Rolls

CANADA

FLOODED DEEP CYCLE BATTERY — S12 GC



Series	4000	Warranty	3 Years
Volts	12	BCI	GC12
Cells	6	Plates/Cell	11
Terminal Type	UTL		
Included Hardware	S/S Hex Cap Screw, Nut, Lock & Flat Washer		
Size & Thread	5/16"-18 x 1-1/2"		

Charge

Charge Voltage Range	14.7-15 V/cell @ 25°C (77°F)
Recommended Charge Current Capacity (String)	15 A
Maximum Charge Current (String)	25 A
Self-Discharge Rate	5%-10% per month at 25°C (77°F)

Capacity

Cold Crank Amps (CCA) 0°F / -17°C	563
Marine Crank Amps (MCA) 32°F / 0°C	703
Reserve Capacity (RC @ 25A)	284 Minutes
Reserve Capacity (RC @ 75A)	79 Minutes

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	**206 AH**	**2.06 A**
@ 72 Hour Rate	**195 AH**	**2.71 A**
@ 50 Hour Rate	**184 AH**	**3.69 A**
@ 20 Hour Rate	**155 AH**	**7.75 A**
@ 15 Hour Rate	**147 AH**	**9.82 A**
@ 10 Hour Rate	**136 AH**	**13.64 A**
@ 8 Hour Rate	**133 AH**	**16.66 A**
@ 5 Hour Rate	**122 AH**	**24.49 A**
@ 1 Hour Rate	**62 AH**	**62 A**

Amphere hour capacity ratings based on specific gravity of 1.280.
Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

Specifications

Certified System™
SAI GLOBAL
ISO 9001 Quality

Weight	37.5 kg	82.5 lbs
Length	33.3 cm	13.13"
Width	18.2 cm	7.17"
Height Inc. Term.	27.4 cm	10.8"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Electrolyte Reserve	38 mm	1.5"
Container	Polypropylene	
Cover	Polypropylene	
Handles	Top Molded Strap Brackets	

Cycle Life vs. Depth of Discharge



Voltage vs. Depth of Discharge



Rev.#1 | March 2019